

## UT200 SERIES

400-600A Digital Clamp Meters




UT201R/202R/202F  
(AC pouze střídavý proud)



UT203R/204R  
(AC/DC proud)



True RMS



Měření nízkého proudu



Měření frekvence  
na vysokých napětích




NCV měření



600V ochrana na všech rozsazích





Parametry	Rozsah	UT201R	UT202R	UT202F	UT203R	UT204R
AC proud (A)	0.04~400A	±(2%+10)	±(2%+10)		±(2%+5)	
	0.06~600A			±(2%+10)		±(2%+5)
AC frekvence proudu (Hz)	50Hz~100Hz	±(1%+5)	±(1%+5)	±(1%+5)		
DC proud (A)	0.04~400A				±(2%+5)	
	0.06~600A					±(2%+5)
AC napětí (V)	600V	±(0.8%+5)	±(0.8%+5)	±(0.8%+5)	±(0.8%+5)	±(0.8%+5)
AC frekvence napětí (Hz)	10Hz~10kHz	±(1%+5)	±(1%+5)	±(1%+5)		
	10Hz~60kHz				±(0.5%+2)	±(0.5%+2)
DC napětí (V)	600V	±(0.5%+2)	±(0.5%+2)	±(0.5%+2)	±(0.5%+2)	±(0.5%+2)
Odpor (Ω)	40MΩ	±(0.8%+2)	±(0.8%+2)		±(0.8%+2)	
	60MΩ			±(0.8%+2)		±(0.8%+2)
Kapacita (F)	4mF		±(4%+5)			
	40mF				±(4%+5)	
	60mF			±(4%+5)		±(4%+5)
Teplota (°C)	-40°C~1000°C		±(1.5%+5)			±(1.5%+5)
Frekvence (Hz)	10Hz~10MHz			±(1%+5)	±(0.1%+4)	±(0.1%+4)
<b>Funkce</b>						
Displej						
Auto rozsah		√	√	√	√	√
Průměr čelisti		28mm	28mm	28mm	28mm	28mm
True RMS		√	√	√	√	√
NCV		√	√	√	√	√
Akustický test		√	√	√	√	√
Test diod		√	√	√	√	√
MAX/MIN		√	√	√	√	√
Relativní režim			√	√	√	√
Nulování					√	√
Data Hold		√	√	√	√	√
Indikace vybité baterie		√	√	√	√	√
Automatické vypnutí		√	√	√	√	√
Napájení	1.5V AAA (R03) x 2					
Velikost displeje	37mm x 25mm					
Barva	Červeno-šedá					
Hmotnost	UT201R/202R/202F: 248g; UT203R/204R: 235g					
Rozměry	215mm x 63mm x 36mm					
Objednávací číslo		0772 0254	0772 0255	0772 0256	0772 0257	0772 0258